

Novo 489 SIM Series

SIM Series

Softener, Ferrous Iron and Manganese Combination Removal

Combining proven water softener capabilities with the ability to remove clear water iron, the 489 SIM Series system provides an effective and economical solution to hard and iron contaminated water. In addition, the system, is specially designed for application in low pH (acidic) water. Hard water contains dissolved calcium and magnesium which build up inside your water heater, plumbing fixtures and appliances. The minerals also react with soap to form a scum which appears as bathtub ring, greys your laundry and leaves your hair dull and your skin itchy. Iron water leaves yellow, orange or brown stains on your laundry, sinks, tubs and toilets.


The 489 SIM Series system contains a bed of specialty ion exchange resin beads. As water passes through the bed, calcium and magnesium, the hardness minerals, and any clear water iron are removed and held by the resin.

Eventually, the resin beads become saturated and must be regenerated. A brine solution is drawn into the bed to drive out the accumulated minerals. This process is called ion exchange. After the minerals and brine are rinsed out with fresh water, the regenerated resin is ready to soften your water again. The demand regeneration control valve includes a metering system which monitors your soft water use, regenerating only when necessary based on your water usage. Consequently, you save salt, water and money.



Specifications	NVO489DFSIM-100	NVO489DFSIM-150	NVO489DFSIM-200	NVO489DFSIM-300*
	15010684	15010685	15010686	15010687
Factory Settings - Iron & Manganese				
Salt Used - Per Regeneration	12.0 lbs	18.0 lbs	24.0 lbs	36.0 lbs
Water Used - Regeneration	124 gal ± 10%	215 gal ± 10%	274 gal ± 10%	278 gal ± 10%
Hardness Removal - Grains	30,000	45,000	60,000	90,000
Filter Media Volume (ft3)	1.0 ft ³	1.5 ft ³	2.0 ft ³	3.0 ft ³
Garnet	Yes	Yes	Yes	Yes
Tank Size	10x54	12x52	13x54	14x65
Tank Jacket	Yes	Yes	No	No
Media Loaded	Yes	Yes	No	No
Brine Tank Size (Inches)	18.1 x 34.5	20.3 x 37.4	20.3 x 37.4	23.0 x 40.5
Salt Storage Capacity	270 lbs	350 lbs	350 lbs	420 lbs
Flow Rate @ 15 psi Pressure Drop	11.0 gpm	11.2 gpm	12.2 gpm	12.6 gpm
Flow Rate @ 25 psi Pressure Drop	15.0 gpm	15.1 gpm	16.2 gpm	16.6 gpm
Back Wash Flow Rate	2.4 gpm	4.0 gpm	5.0 gpm	5.0 gpm
Shipping Weight	120 lbs	164 lbs	214 lbs	300 lbs
Regeneration Type	Co-Current / Down Flow			
Maximum Hardness	75 Grains Per Gallon			
Maximum Total Iron: Total iron = iron x 1 plus manganese x 2	pH <7.2 - 10.0 ppm Total Iron; pH >7.2 - 7.0 ppm Total Iron			
Maximum Manganese (See Total Iron)	5.0 ppm			
Resin Type	Fine Mesh			
Plumbing Connections	Comes with 1" 90 degree elbow connectors			
Electrical Requirements	Input 120V 60 Hz - Output 12V 650mA			
Water Temperature	Min 39 - Max. 100° F			
Water Pressure	Min. 20 - Max. 125 psi			

*Media not loaded in mineral tank.



SIM Series includes Pro Easy Feeder Starter Kit.



Your Local Plumbing Professional

Toll Free: 877-288-9888
www.novowater.com

Regina, SK • Cambridge, ON • Whitestown, IN
 Houston, TX • Phoenix, AZ • Guadalajara, MX

80155089 2023-12-19
 Download only